

ECOTANK+ 1.2 / 2.5

Centrifugal tank pump for the removal of condensates from air conditioners, refrigerated displays or gas condensing boilers.

Ref ECOTANK+ 1.2: DE12QCC610
Ref ECOTANK+ 2.5: DE25QCC620



pH > 2.5



pH > 2.5



Specifications

| | |
|--------------------------------|--------------------|
| Flowrate max | 300 l/h |
| Discharge head max | 4.6 m |
| pH tolerated | pH > 2.5 |
| Max temperature of condensates | 40°C |
| Electrical power | 65W |
| Voltage | 230V 50Hz |
| Alarm | NO-NC 3A |
| Noise level | N/C |
| Protection rating | IP20 |
| Thermal protection | Yes |
| Operating cycle* | 30% |
| Power cable lenght | 1.5 m |
| Dimensions ECOTANK+ 1.2 | 280 x 130 x 129 mm |
| ECOTANK+ 2.5 | 280 x 130 x 159 mm |

* The pump is able to run 30% of the time if necessary. (ex 3s ON / 7s OFF)

Benefits



Universal electric plug

Power/alarm cable can be taken off, making easy installation and maintenance.



Outlet for 6/9 or 9/12 mm tube

Thanks to its connector supplied, the discharge can be made with a 6/9mm or a 9/12mm tube.



High capacity tank

Thanks to its 2.5 l tank, the ECOTANK+ 2.5 reduces the number of pumping cycles and answers to a great deal of applications.



Compact tank pump

With only 129mm height, the ECOTANK+ 1.2 fits easily in any space.



Reversible tank

Turning the tank allows to fit in any configuration.

Pack contents



Pump - Cable power / alarm - 6/9mm outlet adaptor - Screws and rawlplugs

Flowrate

